



START PAC

SUPERIOR TECHNOLOGY. SUPERIOR SUPPORT.

Call us Toll Free
1-888-901-9987
www.StartPac.com

Model Li2800QC Twin Pac – 28.5 VDC - Patent Pending



DESCRIPTION

This powerful portable Lithium Ion starting unit is a full 28VDC battery Twin Pac and will provide superior starts on all electrically-started turbine engines. This versatile Twin Pac can be used as a single unit or separated for two complete Lithium units that can be easily carried on board. The Li2800QC Twin Pac has redundant chargers with a total of 14 amps output and a recharge time of approximately 4 hours.

SPECIFICATIONS

- 56 AMP hours @ 10 hour Rate
- 2400 AMPS Peak Current
- L 38.4" x W 7.5" x H 9.75"/L 98cm x W 19cm x H 24cm
- 120 lbs./ 55 kilos Complete
- Not to be used as an aircraft battery charger.

FEATURES

The all new patent pending Start Pac® Model Li2800 QC Twin Pac utilizes the latest technology in Lithium batteries. These batteries provide the same power as the lead-acid type but are 42% lighter and 32% smaller. In addition, lithium batteries have two other major advantages:

1. Twice the battery life of lead-acid batteries
2. No sulfation problems (can be left in a discharged state without causing damage)

Please Note: Lithium ion batteries can be damaged by deep discharges. Do not run the batteries down below 24 volts, a spike during a start is okay. Voltages below 24 begin the damage to the batteries. At 20 volts, the batteries will be damaged beyond repair.

Batteries have no memory effect and can be recharged at anytime. Made in the USA.
CE Certified. CE marked if purchased through Airpart UK.

All Start Pac™ products come with a 1-year warranty on workmanship and materials. Batteries are cycle-dependent and therefore are not covered under this warranty.

Please handle this unit in a responsible manner. Start Pac™ is not responsible for damages caused by misuse or neglect.